



Sicad s.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL PVC 350

DESCRIPTION

Single sided packaging tape.

PRODUCT DATA

Backing	0.037 mm PVC film; available in several colours (0.039mm black and orange fluo colour version)
Adhesive	Natural rubber and resins

	Unit	Value	Method
Total thickness	mm	0.058 (0.060 black and orange fluo colour version)	PSTC 133
Adhesion to steel	N/25mm	4.5	PSTC 101
Tensile strength MD	N/25mm	125 (130 black and orange fluo colour version)	PSTC 131
Elongation at break	%	70	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Single sided carton sealing tape. The wide colour range makes this tape suitable for bag sealing/colour coding in retailing.

Features	Benefits	
Natural rubber and resins adhesive	✓ Good adhesion in several applications	✓ Performing even at low temperature
Coloured PVC backing	✓ Well adaptable to different shapes ✓ Good elongation	✓ Colour coding ✓ Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PA013EN_REV04_PVC350