

Matière :


Corps en laiton
Joint en NBR

Conception :

Selon la norme française NF E29-573
Griffes Ø41
Joint à lèvres Ø15
Filetage BSPP selon ISO 228-1
Collerette avec butée anti-rotation (embout cannelé)


Caractéristiques techniques :

PN 10 bar
Températures : -10/+70 °C

**510/710
Raccord cannelé**



Référence	L	Ø tuyau	pois 510	pois 710
200xxx0000600	55.5	6-7	0.082	0.077
200xxx0000900	64.5	9-11	0.094	0.089
200xxx0001100	64.5	11-13	0.098	0.093
200xxx0001300	64.5	13-15	0.103	0.098
200xxx0001600	64.5	16-18	0.108	0.103
200xxx0001900	64.5	19-21	0.114	0.109
200xxx0002200	64.5	22-24	0.118	0.113
200xxx0002500	64.5	25-27	0.135	0.130
200xxx0003000	64.5	30-32	0.146	0.141

xxx :
510 = livré avec joint NBR monté
710 = livré sans joint

**511/711
Raccord taraudé**



Référence	G	L	pois 511	pois 711
200xxx0000800	G 1/4"	29	0.081	0.076
200xxx0001200	G 3/8"	29.5	0.081	0.076
200xxx0001500	G 1/2"	31	0.084	0.079
200xxx0002000	G 3/4"	32	0.086	0.081
200xxx0002600	G 1"	33	0.094	0.089
200xxx0003300	G 1"1/4	38	0.130	0.125

xxx :
511 = livré avec joint NBR monté
711 = livré sans joint

**512/712
Raccord fileté**


Référence	G	L	pois 512	pois 712
200xxx0000800	G 1/4" - B	34	0.083	0.078
200xxx0001200	G 3/8" - B	35	0.087	0.082
200xxx0001500	G 1/2" - B	37.5	0.094	0.089
200xxx0002000	G 3/4" - B	38.5	0.104	0.099
200xxx0002600	G 1" - B	42	0.128	0.123
200xxx0003300	G 1"1/4 - B	42	0.145	0.140

xxx :
512 = livré avec joint NBR monté
712 = livré sans joint

**513/713
Bouchon de fermeture**


Référence	L	pois 513	pois 713
200xxx0000000	29	0.078	0.073

xxx :
513 = livré avec joint NBR monté
713 = livré sans joint