



Application :

Use for :

- Acier / Steel < 800 N/mm²
- Fonte / Cast Iron
- Aluminium
- Acier dur / Hard steel < 900 N/mm²
- Inox / Stainless Steel 304L - 316L

MF					
M3	0,35	2,65	40	4	3
M4	0,35	3,65	45	5	3
M4	0,50	3,5	45	5	3
M5	0,50	4,5	50	6	5
M5	0,75	4,25	50	6	5
M6	0,50	5,5	50	6	5
M6	0,75	5,25	50	6	4,9
M7	0,75	6,25	50	6	4,9
M8	0,5	7,5	50	6	4,9
M8	0,75	7,25	50	6	4,9
M8	1,00	7	56	6	4,9
M9	0,75	8,25	56	7	5,5
M9	1,00	8	63	7	5,5
M10	0,75	9,25	63	7	5,5
M10	1,00	9	63	7	5,5
M10	1,25	8,75	70	7	5,5
M11	1,00	10	63	8	6,2
M11	1,25	9,75	63	8	6,2
M12	0,75	11,25	70	9	7
M12	1,00	11	70	9	7
M12	1,25	10,75	70	9	7
M12	1,50	10,5	70	9	7
M13	1,00	12	70	11	9
M13	1,50	11,5	70	11	9
M14	0,75	13,25	70	11	9
M14	1,00	13	70	11	9
M14	1,25	12,75	70	11	9
M14	1,50	12,5	70	11	9
M15	1,00	14	70	12	9
M15	1,50	13,5	70	12	9
M16	1,00	15	70	12	9
M16	1,25	14,75	70	12	9
M16	1,50	14,5	70	12	9
M18	1,00	17	80	14	11
M18	1,25	16,75	80	14	11
M18	1,50	16,5	80	14	11
M18	2,00	16	80	14	11

MF

DIN2181

Référence

BB210

Référence / Code BB210

Nuance / Material HSS

Tolérance / Tolerance ISO 6H

Coupe à (R / L) Droite (R)

Goujure / Flute Droite / Straight

Entrée / Tap point A - C

Pour trou / For hole

